

Technical Specifications

Endura-3	
Sensor Port Capacity	3
Data Communications	Wifi (USB-C backup)
Housing Material	Acetal (500 m)
Protective Cage Material	Stainless Steel
Dimensions	Sm Cage: 370 x 76 mm Md cage: 426 x 76 mm Lg Cage: 497 x 76 mm
Weight in Air	1.5 kg
Weight in Water	0.8 kg
Wireless Charger Connector Type	MCBH6M
Wireless Charger Input Voltage	18-28VDC

Key Features

Three X2•Series Interchangeable Ports

Custom configure a single instrument for multiple applications

Connector Free Operation

Charge wirelessly, or use the USB connector for convenience in the workshop

No Radial Alignment Requirements

Pull the instrument into the charger and it will charge wirelessly every time

Unparalleled Reliability

Minimize wear and tear with no connectors or cabling on the solution

Integrated WiFi

Transfer data wirelessly

Sailfish Software

Configure, download, process and export profiles automatically

Technical Specifications

Endura-6	
Sensor Port Capacity	6
Data Communications	Wifi (USB-C backup)
Housing Material	Acetal (500 m)
Protective Cage Material	Stainless Steel or CuNi
Dimensions	600 x 100 mm
Weight in Air	4.1 kg
Weight in Water	2.1 kg
Wireless Charger Connector Type	MCBH6M
Wireless Charger Input Voltage	18-28VDC

Key Features

Six X2•Series Interchangeable Ports

Custom configure a single instrument for multiple applications

Connector Free Operation

Charge wirelessly, or use the USB connector for convenience in the workshop

No Radial Alignment Requirements

Pull the instrument into the charger and it will charge wirelessly every time

Unparalleled Reliability

Minimize wear and tear with no connectors or cabling on the solution

Integrated WiFi

Transfer data wirelessly

Integrated UV Biofouling Control

Seamlessly integrate non-toxic and non-contact UV biofouling control with AML instrumentation

Sailfish Software

Configure, download, process and export profiles automatically